

Saab 9-3 Walbro Fuel Pump B207 & Z18XE (MY04 onwards) Fitting Instructions



- 1) **BEFORE REMOVAL OF THE FUEL TANK OR PUMP, PLEASE READ THE SAFETY INSTRUCTIONS ON THE ENCLOSED LEAFLET.**
- 2) Drop the fuel tank.
- 3) Remove the two fuel hoses and the electrical connector from the fuel pump cover.
- 4) Unscrew the fuel pump cover and from the underside unplug the electrical connectors.
- 5) Prise off the clip holding the delivery hose from the underside of the fuel pump cover and remove the hose.
- 6) With the canister remaining in the fuel tank, prise in the three lugs of the white insert (as shown above) and lift up the old fuel pump from the canister.
- 7) Unclip the electrical connector from the old fuel pump and swap over to the short harness connector of the new fuel pump.
- 8) Install the new fuel pump into the canister (it will only fit one way so rotate as necessary). When fitted correctly the three lugs will lock the fuel pump into the canister. **CHECK THAT THE PUMP IS LOCKED IN.**
- 9) Attached the new delivery hose, the electrical connectors for the fuel pump and level sender to the underside of the fuel pump cover.
- 10) Screw down the fuel pump cover using a new tank seal